

Gegenmuttern



Material:


Polycarbonat

Temperaturbereich:

-40°C bis 120°C

Farbe(n)/Ausführungen:

- grau



Locknuts

Material:


Polycarbonate

Temperature range:

-40°C to 120°C

Colour(s)/Designs:

- grey



SW SW	Gewinde Thread	m m	D D	Art.-Nr. Art. no.	VE Stck. PU pcs.
15,0	PG 7	4,5	16,5	7001070	50
19,0	PG 9	4,5	21,0	7001096	50
22,0	PG 11	5,0	24,0	7001118	50
24,0	PG 13,5	5,5	26,0	7001134	50
27,0	PG 16	6,0	30,0	7001169	50
32,0	PG 21	6,5	35,0	7001215	20
41,0	PG 29	7,5	44,0	7001290	20
55,0	PG 36	8,5	60,0	7001363	10
60,0	PG 36	8,0	60,0	7001363	10
65,0	PG 42	9,0	71,0	7001428	5
69,5	PG 48	9,5	76,0	7001487	5

Flachdichtungen



Material:


Perbunan/Neopren

Temperaturbereich:

-25°C bis 80°C

Farbe(n)/Ausführungen:

- schwarz



Flat Sealings

Material:

Perbunan/Neoprene

Temperature range:

-25°C to 80°C

Colour(s)/Designs:

- black



D D	d d	s s	Material Material	Art.-Nr. Art. no.	VE Stck. PU pcs.
17,0	10,0	1,0	Perbunan	8113352	1000
17,0	12,0	2,0	Perbunan	8113416	1000
20,0	13,0	1,0	Perbunan	8113017	1000
21,0	10,0	2,0	Perbunan	8113092	lose/lose
24,0	16,0	2,0	Perbunan	8113084	1000
24,0	18,0	1,0	Perbunan	9805281	1000
25,0	21,0	2,2	Neopren/Neoprene	8113424	lose/lose
25,5	16,0	3,0	Perbunan	8113327	lose/lose
28,0	16,0	2,0	Perbunan	8113076	lose/lose
28,0	21,0	1,0	Perbunan	8113025	1000
28,0	21,0	2,0	Perbunan	8113041	1000
34,0	16,0	2,0	Perbunan	8113319	1000
35,0	25,0	2,0	Perbunan	8113050	1000
40,0	26,0	2,0	Perbunan	8113068	1000
42,0	33,0	2,0	Neopren/Neoprene	8113010	lose/lose

5.3