

PP GM

Normalprofil
AHW
High Flex
UFW

RoHS

Material:
Polypropylen GM

Temperaturbereich:
3000 h: -40°C bis 105°C
240 h: -40°C bis 125°C

Flammschutz:
• UL 94: HB
• nach FMVSS 302: selbstverlöschend


Farbe(n)/Ausführungen:
• Schwarz, weitere auf Anfrage
• Stücklängen auf Anfrage

PP GM

Normal Profile
AHW
High Flex
UFW

Eigenschaften:
• Hohe Wärmeformbeständigkeit
• Enorme Kälteschlagzähigkeit
• Hohe Zähigkeit
• Biegewechselbeständig
• Sehr gute chemische Beständigkeit
• UV-beständig nach DIN EN ISO 8580

Anwendungsbereiche:
• Fahrzeugbau
• AHW-Profil: für kleine Biegeradien besonders geeignet



Material:
Polypropylene GM
Temperature range:
3000 h: -40°C to 105°C
240 h: -40°C to 125°C

Inflammability:
• UL 94: HB
• acc. to FMVSS 302: selfextinguishing

Colour(s)/Designs:
• Black, others on request
• Cutted lengths on request

Characteristics:
• Great shape permanence to heat
• Enourmous cold impact strength
• High strength
• Bending stabile
• Excellent chemical resistance
• UV resistant acc. to DIN EN ISO 8580

Applications:
• Vehicle Industries
• AHW-Profile: for small bending radii recommended

NW	Profil	A mm	I mm	Container / Container				Ring / Coil		
				Art.-Nr. geschlitzt schwarz	VE m	Art.-Nr. ungeschlitzt schwarz	VE m	Art.-Nr. geschlitzt schwarz	Art.-Nr. ungeschlitzt schwarz	VE m
NW	profile	A mm	I mm	Art. no. slit black	PU m	Art. no. unslit black	PU m	Art. no. slit black	Art. no. unslit black	PU m
3	Normal/normal	5,1	2,8	1930503	18000	1930903	18000	1929653	1929703	200
4,5	Normal/normal	7,1	5,0	1930504	10000	1930904	9000	1930804	1930854	100
6	Normal/normal	9,2	6,0	1930506	5000	1930906	5000	1930806	1930856	100
7,5	Normal/normal	9,9	6,9	1930507	5000	1930907	5000	1930807	1930857	50
8,5	Normal/normal	11,6	8,5	1930508	4000	1930908	3300	1930808	1930858	50
10	Normal/normal	12,7	10,1	1930510	3300	1930910	3000	1930810	1930860	50
12	Normal/normal	15,6	12,0	1930512	2200	1930912	2200	1930812	1930862	50
13	Normal/normal	15,8	12,9	1930513	2200	1930913	2000	1930813	1930863	50
14	Normal/normal	18,3	14,5	1930514	1700	1930914	1700	1930814	1930864	50
16	Normal/normal	18,8	15,2	1930516	1700	1930916	1500	1930816	1930866	50
17	Normal/normal	21,0	16,8	1930517	1300	1930917	1100	1930817	1930867	50
19	Normal/normal	24,0	19,4	1930519	1000	1930919	700	1930819	1930869	50
22	Normal/normal	25,5	21,8	1930522	900	1930922	700	1930822	1930872	50
23	Normal/normal	28,0	23,7	1930523	700	1930923	650	1930823	1930873	50
26	Normal/normal	31,3	26,4	1930526	550	1930926	500	1930826	1930876	25
29	Normal/normal	33,9	29,3	1930529	500	1930929	450	1930829	1930879	25
37	Normal/normal	42,0	36,7	1930537	300	1930937	250	1930837	1930887	25
50	Normal/normal	53,6	47,8	1930550	200	1930950	150	1930850	1930890	25
4,5	AHW/AHW	7,1	5,0	1929604	10000	1929754	9000	1929654	1929704	100
6	AHW/AHW	9,2	6,0	1929606	5000	1929756	5000	1929656	1929706	100
8,5	AHW/AHW	12,9	8,5	1929608	3300	1929758	3000	1929658	1929708	50
11	AHW/AHW	15,7	11,1	1929611	2200	1929761	2000	1929661	1929711	50
15	AHW/AHW	21,2	15,0	1929615	1300	1929765	1100	1929665	1929715	50
19	AHW/AHW	25,7	19,1	1929619	900	1929769	700	1929669	1929719	50
26	AHW/AHW	31,4	26,3	1929626	500	1929766	450	1929676	1929726	25
34	AHW/AHW	39,5	34,1	1929634	300	1929774	200	1929684	1929734	25
13	High Flex/High Flex	18,4	13,9	1939153	1700	1939143	1700	1939053	1939043	50
19	High Flex/High Flex	24,0	18,8	1939159	900	1939149	700	1939069	1939059	50
23	High Flex/High Flex	28,5	23,5	1939173	600	1939163	500	1939073	1939063	50
4,5	UFW/UFW	7,2	4,7	1952304	10000	1952204	9000	1952104	1952004	100
7,5	UFW/UFW	10,0	6,4	1952307	5000	1952207	5000	1952107	1952007	50
8,5	UFW/UFW	11,9	8,4	1952308	4000	1952208	3300	1952108	1952008	50
10	UFW/UFW	13,0	9,3	1952310	3300	1952210	3000	1952110	1952010	50
13	UFW/UFW	15,8	12,4	1952313	2200	1952213	2000	1952113	1952013	50
17	UFW/UFW	21,1	16,2	1952317	1300	1952217	1100	1952117	1952017	50
19	UFW/UFW	23,6	18,8	1952319	900	1952219	700	1952119	1952019	50
22	UFW/UFW	25,5	20,1	1952322	800	1952222	700	1952122	1952022	50
23	UFW/UFW	28,5	22,6	1952323	700	1952223	650	1952123	1952023	50
26	UFW/UFW	31,4	25,1	1952326	600	1952226	600	1952126	1952026	25
29	UFW/UFW	34,5	28,5	1952329	500	1952229	450	1952129	1952029	25
37	UFW/UFW	42,2	35,5	1952337	300	1952237	250	1952137	1952037	25