

4		3		2		1							
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		LOC		DIST		REVISIONS					
© COPYRIGHT - By -		ALL RIGHTS RESERVED.		G		14		P	LTR	DESCRIPTION	DATE	DWN	APVD
									G	REVISED PER ECO-14-015185	04DEC2014	NK	DR

BODY

INSULATION

SERRATIONS

2

.620 MAX

.031 MIN DIA


.104 MAX

1 FOR .050 TO .080 WIRE INSULATION DIA.

2 BRAZED SEAM ON BUTT SPLICE BODY.

3 MATERIAL: INSULATION - PVC
COLOR - YELLOW, TRANSPARENT
BODY - COPPER PER ASTM B152
FINISH - TIN PL. PER ASTM B545

100	LOOSE PIECE	8-321026-1
4000	ON TAPE	2-321026-1
1000	LOOSE PIECE	321026
QTY	DESCRIPTION	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN jr_ruth 27OCT04	 TE Connectivity						
DIMENSIONS: INCHES		CHK T MICHIELUTTI 27OCT04							
		APVD T MICHIELUTTI 27OCT04	NAME WIRE BUTT SPLICE, PLASTI-GRIP, WIRE SIZE: 26-22						
		PRODUCT SPEC -							
MATERIAL 3		APPLICATION SPEC 114-2161	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO -			
		WEIGHT -	A300779		C-321026				
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .008 4 PLC ± - ANGLES ± 5° FINISH 3		CUSTOMER DRAWING					SCALE 1:1	SHEET 1 OF 1	REV G