Kabelverschraubung SCHLEMMER-TEC

Messing vernickelt
PG-Gewinde, kurz

Cable gland SCHLEMMER-TEC

nickel-plated brass
PG-thread, short



RoHS | IP 68

Material:
- 1/3: Verschraubungskörper/ Hutmutter: Messing vernickelt
- 2: Klemmkörper: Polyamid 6
- 4: Dichtring für Außengewinde: Nitril
- 5: Dichtung: Neopren

Temperaturbereich:
-40°C bis 100°C

Farbe(n)/Ausführungen:
- Außengewinde: PG
- kurzes Gewinde
- Reduzier-Dichteinsatz

Eigenschaften:
- optimale Zugentlastung durch Klemmlamellen
- gas- und wasserdicht
- zusätzlicher Dichtring (4) aus Nitril am Verschraubungskörper

Zubehör (siehe Kapitel…):
- Gegenmuttern (3.3)
- Montagezange Mon.Za (3.1)

Anwendungsbereiche:
- Maschinen- und Anlagenbau
- Photovoltaik
- Automatisierungstechnik

Material:
- 1/3: Gland element/Cap nut: nickel-plated brass
- 2: Clamping shell: Polyamide 6
- 4: Sealing-Ring for External thread: Nitrile
- 5: Sealing: Neoprene

Temperature range:
-40°C to 100°C

Colour(s)/Designs:
- External thread: PG
- short thread
- reduction sealing insert

Characteristics:
- maximum strain relief through clamp lamella
- gas and water-tight
- additional Nitrile sealing-ring (4) on the gland element

Accessories (see chapter…):
- lock nuts (3.3)
- Mounting tool Mon.Za (3.1)

Applications:
- Machine and apparatus construction
- Photovoltaic
- Automation technology

Außengewinde External thread	Klemmbereich mm Clamping range mm	Gewindelänge (E) mm Thread length (E) mm	SW mm SW mm	Art.-Nr. vernickelt Art. no. nickel-plated	VE Stck. PU pcs.
PG 7	2,5 - 6,5	5,0	14,0	4220307	50
PG 9	4,0 - 9,5	6,0	17,0	4220309	50
PG 11	6,0 - 11,5	6,0	20,0	4220311	50
PG 13,5	7,0 - 13,0	6,5	22,0	4220313	50
PG 16	8,0 - 15,0	6,5	24,0	4220316	50
PG 21	11,0 - 19,0	7,0	30,0	4220321	20
PG 29	16,0 - 26,0	8,0	40,0	4220329	20
PG 36	22,0 - 34,5	9,0	50,0	4220336	10
PG 42	27,0 - 40,0	10,0	58,0	4220342	5
PG 48	35,0 - 48,0	10,0	65,0	4220348	5
mit Reduzier-Dichteinsatz / with reduction sealing insert					
PG 7 RED	1,5 - 5,0	5,0	14,0	4220351	50
PG 9 RED	2,5 - 7,0	6,0	17,0	4220352	50
PG 11 RED	3,0 - 8,5	6,0	20,0	4220353	50
PG 13,5 RED	4,0 - 10,0	6,5	22,0	4220354	50
PG 16 RED	5,0 - 12,0	6,5	24,0	4220355	50
PG 21 RED	8,0 - 16,0	7,0	30,0	4220356	20
PG 29 RED	11,0 - 21,0	8,0	40,0	4220357	20
PG 36 RED	16,0 - 28,0	9,0	50,0	4220358	10
PG 42 RED	22,0 - 34,0	10,0	58,0	4220359	5
PG 48 RED	28,0 - 40,0	10,0	65,0	4220360	5