

enclosures **size "21.21"**

**insulating type** ..... page: 153 ÷ 154  
**metallic type** ..... page: 155 ÷ 156  
**aggressive environments**..page: 157  
**EMC** ..... page: 158

- features according to EN 61984:  
**10A 250V 4kV 3**
- UL, CSA, CCC, GL certified
- for maximum current load, see the insert load curve section on page 28
- inserts and enclosures for applications with temperatures up to 180 °C, available on request
- can be mated with CKS inserts

**inserts, 3 poles + ⊕  
 screw terminal connections**




**inserts, 4 poles + ⊕  
 screw terminal connections**




description	part No.	part No.	part No.	part No.
distinctive colour female inserts with female contacts <sup>1)</sup> male inserts with male contacts	white <b>CKF 03</b> <b>CKM 03</b>	black <b>CKF 03 N</b> <b>CKM 03 N</b>		
distinctive colour female inserts with female contacts <sup>1)</sup> male inserts with male contacts			white <b>CKF 04</b> <b>CKM 04</b>	black <b>CKF 04 N</b> <b>CKM 04 N</b>

<sup>1)</sup> the female inserts can be mounted into the straight bulkhead housings CK I from the rear

dimensions in mm




contacts side (front view)



- inserts for connectors with the following sections:  
 0.75 ÷ 2.5 mm<sup>2</sup> - AWG 18 ÷ 14
- torsion couple recommended for conductor fastening screws and stripping length see section feature of inserts on page 13

dimensions in mm



contacts side (front view)



- inserts for connectors with the following sections:  
 0.75 ÷ 2.5 mm<sup>2</sup> - AWG 18 ÷ 14
- torsion couple recommended for conductor fastening screws and stripping length see section feature of inserts on page 13

dimensions indicated are not binding and may be changed without notice