

Modular Plugs, Accessories and Tooling

External Strain Reliefs For Modular Plugs

FEATURES

- Metal strain relief that positively engages plug housing
- PRO-CRIMPER Tool and Die Set reference will be noted in tooling section
- For use with 8-position Category 3, 5 and 5e Modular Plugs only
- RoHS compliant



ORDERING INFORMATION

Description	Part Number
Not for use with Modular Plug Boots	558527-1
For use with Modular Plug Boots	558527-3

Category 5 and 3, 8-Position Modular Plugs

- Each Kit includes
 - (1) Modular plug Assembly
- Packaged either 500 or 100 to bag
- Use appropriate size modular plug boot for cable diameter



8-Position
Round, Standard



8-Position
Flat, Standard



Shielded 8-Position
Round, Standard

ORDERING INFORMATION

Shielding	Cable Type	Cable Jacket O.D.	Conductor type	AWG	Insulation O.D.	Body Type	Quantity Per Box	Part Number
Unshielded	Round	0.210" (5.33 mm) max.	Stranded	26-28	0.029" to 0.039" (0.74 mm to 0.99 mm)	Standard	100*	5-554169-3
			Solid	24-26	0.029" to 0.039" (0.74 mm to 0.99 mm)	Long	500	5-554169-2
	Flat Oval	0.200" (5.08 mm)	Stranded	26-28	0.029" to 0.039" (0.74 mm to 0.99 mm)	Long	100*	5-557315-3
							500	5-557315-2
			Solid	24-26	0.029" to 0.039" (0.74 mm to 0.99 mm)	Standard	100*	5-554739-3
							500	5-554739-2
Shielded	Round	0.100" x 0.350" (2.54 mm x 8.89 mm) max.	Stranded	26-28	0.035" to 0.039" (0.89 mm to 0.99 mm)	Long	100*	5-554720-3
							500	5-554720-2
	Round	0.200" (5.08 mm)	Stranded	26-28	0.029" to 0.039" (0.74 mm to 0.99 mm)	Standard	100	5-569532-3
			Solid	24-26	0.029" to 0.039" (0.74 mm to 0.99 mm)	Standard	500	5-569532-2
	Flat Oval	0.110" x 0.355" (2.79 mm x 9.02 mm) max.	Stranded	26-28	0.029" to 0.039" (0.74 mm to 0.99 mm)	Standard	100	5-569530-3
							500	5-569530-2