


D

C

B

A



OPERATION TEMPERATURE	-40~85°C	-40~85°C
DEGREE OF PROTECTION	IP67	IP67
INSULATION RESISTANCE	>100MΩ	>100MΩ
MATERICAL GROUP	II	II
OVERVOLTAGE CATEGOYR	II	II
POLLUTION DEGREE	3	3
RATED CURRENT	3A	3A
RATED VOLTAGE	30V	60V
TECHNICAL DATA	T401000804X-000	T401000803X-000

- NOTES;
- PARTS MATERIAL DATA:SEE TABLE1
 - CONTACT FINISH:
GOLD OVER NICKEL OR SILVER OVER NICKEL
 - CABLE WIRES:
26AWG/0.14mm² Min & 24AWG/0.25mm² Max
 - ALL DIMENSIONS ARE FOR NOMINAL REFERENCE ONLY UNLESS OTHERWISE STATE
 - PACKAGIN: 1 PIECE IN A BAG
 - PN INFORMATION FOR ASSEMBLY PARTS
T401000XXXX-000

- CONTACT FINISH:
1:GOLD OVER NICKEL
2:SILVER OVER NICKEL
- NUMBERS OFPINS:
03:3 PINS
04:4 PINS
...
- CABLE OUTLET:
8:PLASTIC(CABLE FEED:3.5~4.8mm)
9:METAL(CABLE FEED:3.5~5.0mm)
...

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASED	11APR2016	L.Z	X.X
	B	EC-16-011351 NEW REVISE	01JUL2016	L.Z	X.X
	B1	REVISED PER ECR-16-012993	18SEP2016	L.Z	X.X
	C	ECR-17-011756	21SEP2017	S.C	C.W







TABLE1

PBT	PRESS SCREW	6
PBT	STRAIGHT PLASTIC HOUSING	5
BRASS	M8 SCTREW ASSY REC TERMINAL	4
BRASS	M8 SCREW ASSY OUT SCREW	3
BRASS	M8,FEMALE INSERT NUT	2
PA	M8,FEMALE HSG,A CODE,4PIN	1
	M8,FEMALE HSG,A CODE,3PIN	
MATERIAL	DESCRIPTION	ITEM

T4010008042-000	RPC-M8-FS-4CON-PG7-M	OBSOLETE
T4010008041-000	RPC-M8-FS-4CON-PG7-MU	
T4010008032-000	RPC-M8-FS-3CON-PG7-M	OBSOLETE
T4010008031-000	RPC-M8-FS-3CON-PG7-MU	
TE PN	TYPE	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN LEAR ZHANG CHK KOBBY ZHAO APVD XU XIANG	12APR2016 12APR2016 12APR2016	TE Connectivity	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±0.20 2 PLC ±0.20 3 PLC ±0.20 4 PLC ±- ANGLES ±- FINISH		NAME M8 FEMALE SCREW ASSY STRAIGHT UNSHIELDING CONNECTOR	
MATERIAL - -		PRODUCT SPEC 108-106140 APPLICATION SPEC 114-137144-1 WEIGHT -		SIZE A2	RESTRICTED TO -
CUSTOMER DRAWING		SCALE 2:1	SHEET 1	OF 1	REV C

- 注意事项;
- 零件材料参见附表1
 - 表面处理:镀金
 - 适用线材:26AWG/0.14mm² Min & 24AWG/0.25mm² Max
 - 所有尺寸标注为基本参考,除非其它说明
 - 包装:每BAG装1PC
 - 料号数字代码参考上表