POLYFLEX®

PA6 Schwer

Normalprofil
Grob

RoHS

Material:
Polyamid 6

Temperaturbereich:
3000 h: -40°C bis 120°C
240 h: -40°C bis 150°C

Flammschutz:
- UL 94: HB
- nach FMVSS 302: < 100 mm/min.

Farbe(n)/Ausführungen:
- Schwarz, weitere auf Anfrage
- Stücklängen auf Anfrage

POLYFLEX®

PA6 Heavy

Normal Profile
Rough

Eigenschaften:
- Kein Unterwickelband bei Verzweigungen und Kabelenden erforderlich
- UV-beständig
- Halogenfrei

Anwendungsbereiche:
- Für hohe mechanische Belastungen
- Motorraum und Karosserie
- Baumaschinen und Maschinen
- Schiffs- und Bahnbau
- Schaltschränke



Material:
Polyamide 6

Temperature range:
3000 h: -40°C to 120°C
240 h: -40°C to 150°C

Inflammability:
- UL 94: HB
- acc. to FMVSS 302: < 100 mm/min.

Colour(s)/Designs:
- Black, others on request
- Cutted lengths on request

Characteristics:
- No wrapping tape necessary at cable feeders or cable ends
- UV resistant
- Free of halogen

Applications:
- For high mechanical stresses
- Body section and chassis
- Construction machinery and machinery
- Ship- and trainbuilding
- Switch cabinet

				Ring/Coil	
NW NW	Profil profile	A mm A mm	l mm l mm	Art. Nr. ungeschlitzt schwarz Art. no. unslit black	m m
8,5	Normal/normal	11,7	8,2	1214089	50
10	Normal/normal	13,0	9,6	1214100	50
12	Normal/normal	15,7	12,1	1214127	50
14	Normal/normal	18,5	13,7	1214143	50
17	Normal/normal	21,2	16,2	1214178	50
23	Normal/normal	28,3	22,7	1214235	50
23G	Grob/rough	28,3	21,5	1214236	50
29	Normal/normal	34,5	28,4	1214291	25
29G	Grob/rough	34,5	26,9	1214292	25
37	Normal/normal	42,0	35,5	1214375	25
37G	Grob/rough	42,5	35,3	1214376	25
50	Normal/normal	54,0	47,6	1214502	25